


LCS-VN-1		Product Features		
		<ul style="list-style-type: none"> <li>◆ Easy to install and use</li> <li>◆ Clear and smooth video browsing; intelligent transmission giving full play to capabilities of the network</li> <li>◆ Online firmware upgrade, and synchronous updating of the functions and experience</li> <li>◆ Standard H.265 video compression algorithm enabling the transmission of high-definition videos in networks with narrow bandwidth; local high-definition videos with high image quality and low stream supporting smoother presentation without ghosting.</li> <li>◆ Two-way voice intercom supported; echo eliminated; noise suppressed.</li> <li>◆ Compatible with Android; remote real-time monitoring supported with the IOS intelligent terminal</li> <li>◆ 2-megapixel high resolution (1920X1080) for clear picture quality</li> <li>◆ Dual-source lighting for night vision (night vision distance = 7 m) comprising infrared lamp / white-light source; color images available for night vision.</li> <li>◆ The built-in rechargeable lithium battery with long battery life functions for up to 6 months under normal circumstances and can stand by for 12 months.</li> <li>◆ 2.4G Wi-Fi supported (IEEE802.11b/g/n)</li> <li>◆ The image automatically flips with the installation direction of the device (G-SENSOR)</li> <li>◆ Cloud storage, micro SD card (up to 128GB) and mobile phone video recording supported</li> <li>◆ QR code intelligent connection and network allocation supported</li> <li>◆ Supporting human contour detection, activity zone, intelligent push and pet snapshot</li> <li>◆ IP65 dustproof and waterproof design for convenient installation; bracket with 1/4 universal screw and magnetic bracket supported</li> </ul>		
		Specifications		
		Master Processor	SOC	HI3518E V300: A dominant frequency of 900 MHz
			DDR	512M
		Image Sensor	Sensor	1/3" color CMOS Sensor
			Lens	M12, f: 2.8mm, F2.0, 2-megapixel
			Visual Angle	H (horizontal) 95 degrees; V (vertical) 55 degrees; D (diagonal) 110 degrees
			Minimum Illumination	0.01 Lux
		Audio	Input/Output	Two-way voice intercom available (built-in microphone and speaker)
			Audio Compressing Method	AAC
		Video	Video Compressing Method	H.265
			Lighting Frequency	50Hz, 60Hz
			Image Frame Rate	15 fps
			Maximum Image Resolution	1920*1080P
Light Source for Night Vision	Mid-power infrared lamp (850nm in wavelength) / dual-source white-light source with an irradiation distance of 7m			
Network	Wireless Network	2.4G Wi-Fi (IEEE802.11b/g/n), built-in antenna		
	Protocols Supported	TCP/IP, UDP/IP, DHCP, RTMP, MUDP		
	IP Address Supported	Dynamic IP address supported		
AI	Intelligent Features	Human contour detection, activity zone, intelligent push, pet snapshot		
Alarm Methods	Alarm Notification	Alarm push by mobile APP, white light flashing and alarm sound		
Wake-up	Wake-up Method	PIR body induction wake-up, and remote positive wake-up		
Video Recording	Recording Method	Alarm triggered recording, and manual recording		
	Video Storage	Cloud storage, local MICRO SD card, and mobile phone memory		
Indicator Lamps	LED Indicator	RGB tri-color lamp indicating the status of power/network signal/functionality		
Battery	Capacity	1000mAh		
	Removability	Unremovable		
	Battery Life	6 months (provided that 20 10s videos are recorded per day)		
	Standby Time	1 year		
	Charging Voltage	DV 5V±5%/1.5A		
	Charge Time	Within 8 hours		
	Protection Method	IP65 resistance to dust and water; over-current/over-discharge/over-charge/short circuit/charging protection at high & low temperatures		
Power Consumption	Standby Power Consumption	2.4mW (3.8V 0.63mA)		
	Power Consumption of Daytime Operation	1W (3.8V 264mA)		
	Power Consumption of Operation at Night	2.23W (3.8V 588mA)		
Interfaces	Power Supply	1 MICRO USB interface		
	SD Card	1 MICRO SD card (up to 128GB supported)		
	Keys	1 reset key and 1 on/off key		
Installation Method	Installation Method	Magnet and 1/4 universal screw holes		
Environment	Dustproof and Waterproof	IP65		
	Operating Environment	-10~45°C / 0%~80% (no condensation)		
	Storage Environment	-20°C~60° / 0%~90% (no condensation)		
Specifications	Size (LxWxH)	84mm*62mm*92.5mm (with bracket excluded)		
	Net Weight of Bare Machine	Approx. 350g		
	Finished Weight	Approx. 570g		
	Material + Process	ABS + PC		
	Color	White with high gloss		
Certifications	Certificate			