

Ics-ptz-5x

3 inches 5MP dual light source Mini poe IP PTZ camera



Eigenschaften:

- > 1/2,8" Sony Low-Light-CMOS-Sensor
- > max. **5MP** Auflösung 2592 x 1944 Ausgabe
- > geringe Beleuchtung 0,01Lux
- > **5x optisches** Zoomobjektiv
- > Tag/Nacht, AWB/MWB, BLC, HLC, 2D/3D-DNR, Shutter, IR-CUT
- > D-WDR, Spiegeln, Drehen, Entnebeln
- > Multiply Style OSD Overlay, Bewegungserkennung, Privatzonenmaske Privacy
- > RTSP und Onvif 17.06 kompatibel mit vielen NVRs von Drittanbietern
- > H.264/H.265 Dual-Stream-Medienserver
- > Einfach zu bedienender P2P Cloud-Dienst
- > Unterstützt Benutzerauthentifizierung, Videodatenverschlüsselung
- > Unterstützt Alarm-Snapshot zu E-Mail und FTP Multiply WEB-Browser
IE, Firefox 32bit ESR, > PC Client, Mobile APP Fernzugriff
- > Blitzschutz 4000V, Starkes wasserdichtes Gehäuse IP66
- > 6 Stück Array IR Led, IR-Abstand 50-60 Meter
- > 2 Stück weiche und warme Beleuchtungs-LEDs, Lichtabstand 20-30 Meter



Model	lcs-ptz-5x
Camera	
Image Sensor	1/2.8" Sony IMX335 CMOS
Effective Pixels	5 megapixels
Electronic Shutter	AUTO, 1/25s ~ 1/100000s
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto/Manual
AGC/BLC/HLC	Support
DNR	2D/3D DNR
Other	Multi-lines OSD, Motion Detection, Privacy Mask, Mirror
Encode	
Chipset	Sigmastar 337DE
Video Standard	H.265/H.264
Video Resolution	Main Stream: 25fps@5MP(2592x1944),25fps@4MP/3MP,30fps@1080P/720P Sub Stream: D1/VGA(640x480)/360P/QVGA@20fps
Video Bitrates	32Kbps - 8Mbps, VBR/CBR

Audio Standard	G.711-u/G.711-a
OSD Overlay	Title and Time overlay
Led light	
IR Led	6pcs array IR Led
IR Distance	50-60 M
Warm Led	2 pcs soft and warm lighting leds, light distance 20-30 meters
Lens	
Focal length	2.7-13.5mm
Zoom	5x optical zoom
Functions	
Human body detection , High power PoE,two way audio	
PTZ	
Pan/Tilt Range	Pan: 0° ~ 355°; Tilt: 0° ~ 92°
Preset Point	255
Control Speed	Pan: 0.5° ~20° /s; Tilt: 0.5° ~20° /s
Network Services	
Protocol	HTTP/RTSP/FTP/NFS/SMTP/DHCP/NTP, etc.
P2P	Yes
Web	IE , Firefox (32bit esr), etc.
Media	CMS, Android, IOS
ONVIF	17.06 compatible
General	
Network Port	1-RJ45, 100Mbps, PoE 48V in
Power Supply	12 VDC ± 10% 2A
Power Consumption	< 20 W
Operating Temp.	-30°C-(+60)°C , 10%-90%R
Size	H= inkl. Halter 15.5cm / Ø 10.5 cm
Weight	1 kg